

Product DATA



BUONO CUV



INCH	SIZE	LOAD INDEX	SPEED INDEX	RIM WIDTH(inch) Standard/Approved	OD(mm)	SW(mm)	UTQG	ARTICLE NO.
16	265/70R16	112	S	8.0/7.0-9.0	778	272	520 A B	JC334/J4391



INCH	SIZE	LOAD INDEX	SPEED INDEX	RIM WIDTH(inch) Standard/Approved	OD(mm)	SW(mm)	UTQG	ARTICLE NO.
17	265/65R17	112	H	8.0/7.5-9.5	776	272	520 A A	J6516/J4108/JB929
	235/65R17	108(xl)	V	7.0/6.5-8.5	738	240	440 A A	J6587/JB930
	225/65R17	102	V	6.5/6.0-8.0	724	228	440 A A	J6517/J4109/JB931
16	215/65R16	102(xl)	V	6.5/6.0-7.5	686	221	440 A A	J6515/JB932



INCH	SIZE	LOAD INDEX	SPEED INDEX	RIM WIDTH(inch) Standard/Approved	OD(mm)	SW(mm)	UTQG	ARTICLE NO.
18	265/60R18	110	H	8.0/7.5-9.5	775	272	520 A A	J6520/J4113/JB926
	235/60R18	107(xl)	V	7.0/6.5-8.5	739	240	440 A A	J6586/J4390/JC333
17	235/60R17	102	V	7.0/6.5-8.5	714	240	440 A A	J6938/JB928



INCH	SIZE	LOAD INDEX	SPEED INDEX	RIM WIDTH(inch) Standard/Approved	OD(mm)	SW(mm)	UTQG	ARTICLE NO.
20	275/55R20	117	H	8.5/7.5-9.5	810	284	520 A A	J4418/JC403
18	255/55R18	109(xl)	V	8.0/7.0-9.0	737	265	440 A A	J6589/JB924
	235/55R18	104(xl)	V	7.5/6.5-8.5	715	245	440 A A	J6519/J4110/JB925



INCH	SIZE	LOAD INDEX	SPEED INDEX	RIM WIDTH(inch) Standard/Approved	OD(mm)	SW(mm)	UTQG	ARTICLE NO.
20	265/50R20	111(xl)	V	8.5/7.5-9.5	774	277	440 A A	J6518/J4112/JB922
19	255/50R19	107(xl)	V	8.0/7.0-9.0	739	265	440 A A	J6588/J4111/JB923

BRAND

BUONO SPORT

BUONO DRIVE

BUONO CUV

BUONO NEVE

TORMENTA X

JOB & DUTY PRO

Product Data